

Easidew Sampler

Easidew Sampler



-
-
-
-
-
- 1 MPa (10 barg)
- 21 MPa (210 barg)

-
-
-
-
-
-
-
-

Easidew Sampler

1 ~ 5 l/min
1 MPa (10 barg) 21 MPa (210 barg)
0.3 μm 99.5 %
1/4" 6mm PTFE FEP
0.5m
316
5/8" UNF Michell
IP66 (NEMA 4) -40 ~ +60°C
-40 ~ +70°C, 0-95 %RH
1.1 kg 1.3 kg

EA2-SAM	Easidew Sampler (0.3 μm) m-valve & PTFE (10 barg)	/ 6mm (0.24 in)
---------	--	--------------------

9Ug] XYk' Qlad' Yf

9Ug] XYk' Qlad' Yf

'C#8' DH 9 : 9D
'S") a DH 9'

S" " " " " ") '1

'C

'%& @

9Ug] XYk' Qlad' Yf

9Ug] XYk' Qlad' Yf

9Ug] XYk' Qlad' Yf

9Ug] XYk' Qlad' Yf

% ADU f%\$' 6Uf [L'
&% ADU f&%\$' 6Uf [L'

9Ug] XYk' Qlad' Yf

9Ug] XYk' Qlad' Yf

Qlad' Yf
'&\$' aa

9Ug] XYk'
'A* 'l ') ' aa'

DGH p
889号齐来工业城4幢6层D1单元
Tel: +[86] 21 5401 2255, Fax: +[86] 21 5401 2085,
Email: cn.info@michell.com, Web: www.michell.com.cn
密析尔仪表保留不断改进的权利, 对新的参数并不会主动通知。
最新版本请与密析尔人员联系
Issue no: Easidew Sampler_97165_V2.1_CN_0519